FUJITSU

Data Sheet FUJITSU PRIMECENTER M1 19-inch Racks

19-inch Industry Standard Rack Systems

The trend to consolidation as a result of virtualization and optimization require environments that are more flexible and reliable. Decades of data center expirience at Fujitsu result in the latest 19-inch Rack Family. The new Fujitsu PRIMECENTER racks are the foundation for meeting IT data center requirements. The PRIMECENTER Racks are the basis for building perfect data center infrastructures. The PRIMECENTER 19-inch Racks can be used to install Fujitsu solutions as well as third-party products. They meet all requirements for flexibility thanks to the multiple configuration options, cooling and maintenance features. In addition a broad portfolio of optional rack accessories complete the efficient rack infrastructure solutions.

PRIMECENTER M1 19-inch Racks

The Fujitsu PRIMECENTER M1 19-inch Racks are the basis for rack configurations, such as server, storage systems as well as operating controls, such as consoles, switches, power distribution units (PDUs) and uninterruptible power supplies (UPS). As the PRIMECENTER M1 19-inch Racks are based on the industry standards EIA310-D, DIN41494 and IEC 297, they can accommodate commercial products that match such standards. The racks can be extended horizontally and fit into the existing IT scenario.

The PRIMECENTER M1 Racks come as asymmetric and symmetric 700 mm wide versions in 24 and 42 height units as well as symmetric 600 mm wide versions in 16, 24 and 42 height units. The symmetric racks offer up to 4 vertical 19-inch slots on left and right front side which can be used for switches or to guide cables from front to rear. The asymmetric racks provide up to 6 vertical 19-inch slots on left front side and space for the patented sideways Fujitsu cable management in the rear. 80% degree of perforation (approximate) and excellent cable management to optimize air flow for cooling and high heat dissipation. The design of the PRIMECENTER M1 Racks ensures easy service and simple maintenance.



in Features	Benefits			
19-inch standard rack technology	To install Fujitsu Technology Solutions rack servers, storage products and components as well as products from other manufacturers.			
Optimized rack structures	Different rack frames for efficient server, switch, power and cable installation with best possible airflow.			
Design	 Asymmetric rack structure with perfect lateral cable management (700 mm width) or symmetric rack structures (600 mm or 700 mm width) 			
Capacity	as 📕			
Ease of service	One wing design front door and two wing rear door, tool less removable.			
	Retractable anti-tilt protection.			
	Optional factory installation with cabling and final tests.			
Access protection	Front-, rear doors and side panels are lockable.			

Mai

0

D

Ca
 Ea

A

Technical details

Base unit	Order code	Dimensions (W x D x H)	Vertical Slots	Transport Dimensions (W x D x H)	Max. pay load / dynamic load	Net weight
PCR M1 724A (24 U asymmetrical)	S26361- K827-V120	700mm x 1050mm x 1203mm	4	800mm x 1200mm x 1350mm (approx.)	540 kg / 650 kg	89 kg
PCR M1 742A (42 U asymmetrical)	S26361- K827-V140	700mm x 1050mm x 2003mm	6	800mm x 1200mm x 2150mm (approx.)	878 kg / 1000 kg	122 kg
PCR M1 724S (24 U symmetrical)	S26361- K827-V220	700mm x 1050mm x 1203mm	2	800mm x 1200mm x 1350mm (approx.)	540 kg / 650 kg	89 kg
PCR M1 742S (42 U symmetrical)	S26361- K827-V240	700mm x 1050mm x 2003mm	4	800mm x 1200mm x 2150mm (approx.)	878 kg / 1000 kg	122 kg
PCR M1 616S (16 U symmetrical)	S26361- K827-V310	600mm x 1050mm x 847mm		700mm x 1200mm x 1075mm (approx.)	320 kg / 400 kg	64 kg
PCR M1 624S	S26361-	600mm x 1050mm x		700mm x 1200mm x	540 kg / 650kg	82 kg
(24 U symmetrical)	K827-V320			1350mm (approx.)		
PCR M1 642S (42 U symmetrical)	S26361- K827-V340	600mm x 1050mm x 2003mm		700mm x 1200mm x 2150mm (approx.)	888 kg / 1000 kg	112 kg
Rack Infrastructure						
Variants		Symmetrical design 700	mm, 24+2 U	U and 42+6 U, for patente and 42+4 U with standa 4 U and 42 U with space o	rd rack design	
Capacity				d 24 height units plus up height units (depth of incl. cable space). Up t per horizontal, 3.5 kg p height unit, maximum 650 kg.	up to 300 mm height unit o 20 kg load incl. cable s per vertical per horizon	units plus up to 6 vertical ts (depth of up to 300mm space). Up to 20kg load ttal, 3.5kg per vertical t, maximum weight up to
Doors		One-piece front door and cooling. Ergonomic door		ear door with high percen	tage of holes (approx. 80%)	for improved server
Front door		One-piece design front d	oor with erg	onomic handle bar, right	or left hand mounting possi	ble.
Rear door		Twin doors to optimize n One door with cable entr		e space		
Internal depth						
19-inch clearance		450.5 mm +1 mm/-0 mn	N			
Front/rear 19-inch level		740 mm				
Space for cabling		Up to 100 mm on front s Up to 180 mm on rear sig	de			
Cable management and ser	vice	Optimized cable routing Cabling openings in the and in the rear door.				
Maximum load		Up to 10000 N stationary 10000 N dynamic load (r				
Permitted total weight		Up to 10000 N / 1000 kg	for 42U rack	S		
Shipment		Optionally ex works, fully adjusting feet on a shock			g. Shipment including 4 hea	avy-duty castors and 4
Top cover Security		Two break out entries for	external cat	bling		
Protection class		DIN (EN60529) IP20				
Security functions		Lockable front, rear door protection.	and side pa	nels, optional antitilt		
Rack accessories		mounting kits, accessory	kits, shelves		utions; networking compon nonitoring (rack console, KV PDU)	

Environment				
Environmental compliance	Operation: Class 3K3*, 3M2, 3S2			
	Transport: Class 2K2, 2M2. 2M1			
Environmental compliance note	*Possibly restricted by rack components			
Operating relative humidity	15 - 98 %			
Operating environment	FTS 04230 – Guideline for Data Center (installation specification)			
Operating environment link	http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe			
Compliance				
Germany	GS			
Еигоре	EN			
USA/Canada	UL/CSA			
Global	CB			
	RoHS (Substance limitations in accordance with global RoHS regulations)			
	WEEE (Waste electrical and electronical equipment)			
Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National			
•	approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request.			
Compliance link	https://sp.ts.fujitsu.com/sites/certificates			
•				

More information

Fujitsu products, solutions & services

In addition to FUJITSU Server PRIMECENTER M1 19-inch Racks, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Built on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offerings. This allows customers to select from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Server PRIMECENTER M1 19-inch Racks, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. www.fujitsu.com/primergy

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www. fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http:// www.fujitsu.com/fts/resources/navigation/ terms-of-use.html Copyright 2019 FUJITSU LIMITED

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact FUJITSU LIMITED

Website: www.fujitsu.com 2019-04-27 WW-EN All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html Copyright 2019 FUJITSU LIMITED