

Data Sheet

FUJITSU Storage ETERNUS JX60

High-capacity storage subsystem

ETERNUS JX60

A passive subsystem extension is a cost-effective solution as capacity requirements often exceed the internal storage capacity of a server. However, data growth is outpacing the increase in disk capacity and thus more disks are needed requiring more rack space. This is why the Fujitsu Storage subsystem ETERNUS JX60 provides high disk capacity in a minimum space. Up to 60 low-cost 3.5 inch Nearline SAS hard disk drives can be hosted in an enclosure of only four rack height units. A total capacity of 480 Terabytes can be delivered by attaching up to 2 enclosures directly to a server with a small, space-saving footprint.



Features & Benefits

Main Features	Benefits
<p>Quality and reliability</p> <ul style="list-style-type: none"> ■ Direct Attached Storage (DAS) for Intel-based servers with 6 Gbit/s SAS connection ■ Up to 120 large capacity Nearline SAS disk drives enlarge storage capacity by up to 480 Terabyte <p>Innovation and flexibility</p> <ul style="list-style-type: none"> ■ Components like hot plug disk drives and power supply modules can be replaced while the server is running ■ The redundant hot-plug power supply units can be connected with phase redundancy via separate power lines. ■ Optimum and secure cooling of the drives is ensured by two independent fans in each power supply unit and in the fan expander module <p>Ease of use</p> <ul style="list-style-type: none"> ■ Status of the components is signalized by LED displays and light-emitting diodes ■ Drive extension is completely managed by the server and can be used in all usage scenarios with certified PRIMERGY servers ■ The subsystem can be integrated in the standard Fujitsu server management ServerView Suite 	<ul style="list-style-type: none"> ■ Reliable storage capacity for biggest data volume ■ Continuous operation during flexible drive replacements ■ Mix and match of disk drives ■ Easy installation and control of the subsystem

Technical details

General system information

Maximum Disk Drives	120
Max. no. of drive enclosures	2
Supported RAID levels	0, 1, 1+0, 5, 5+0, 6, 6+0
Host Interfaces	SAS 3.0 I/O-module (expander)
Connector Type	1 Port MiniSAS HD (SFF-8644)
Supported PRIMERGY server controller	LSI MegaRAID SAS9286CV-8e SAS RAID 5/6 controller LSI SAS9200-8e 6Gb/s 8ext PCIe FH/LP SAS Controller Fujitsu PSAS CP400e SAS Controller
Maximum Storage Capacity	480 TB
Drive Type	3.5-inch, Nearline SAS, 7.200 rpm (4 TB/ 3 TB /2 TB)
Drive interface	Serial Attached SCSI (6 Gbit/s)

Interfaces

Administration	Web-based graphical user interface
----------------	------------------------------------

Supported configurations

All major host operating systems, servers and business applications
Detailed support matrix:
<http://ts.fujitsu.com/matrixep>

Hardware certification	Windows 2012R2 x64 Storage Spaces Enclosure
------------------------	---

Installation specification

19" rackmount	Yes
Dimension - per rack (W x D x H)	482 x 980 x 176 mm 19 x 38.6 x 6.9 inch
Height Unit standard	4 U
Height Unit Maximum	8 U
Weight	max. 95 kg (209 lb) with hard disk drives
Service Area	Front: 800 mm (31.5 inch) or more Rear: 800 mm (31.5 inch) or more
Power voltage	AC 100 - 120 V / AC 200 - 240 V
Power frequency	50 / 60 Hz
Power supply efficiency	92 % (80 PLUS gold)
Maximum Power Consumption	AC 100 - 120 V: 1300 W (1320 VA)
Maximum Power Consumption	AC 200 - 240 V: 1300 W (1320 VA)
Power phase	Single (phase redundancy possible)

Environment

Maximum Heat Generation	AC 100 - 120 V: 4750: kJ/h AC 200 - 240 V: 4750: kJ/h
Temperature (not operating)	0 - 50 °C
Temperature (operating)	10 - 40 °C (50 - 104 °F)
Humidity (operating)	20 - 80 % (relative humidity, non-condensing)
Humidity (not operating)	8 - 80 % (relative humidity, non-condensing)
Altitude	3,000 m (10,000 ft.)
Sound pressure (LpAm)	43.5 dB(A)
Sound power (LWAd; 1B = 10dB)	6.0 B
Noise notes	measured according to ISO7779 and declared according to ISO9296
Operating environment	FTS 04230 – Guideline for Data Center (installation specification)
Operating environment link	http://docs.ts.fujitsu.com/dl.aspx?id=e4813edf-4a27-461a-8184-983092c12dbe
Product safety	UL 60950-1, CSA-C22.2 No. 60950-1, EN 60950-1, IEC 60950-1

Electromagnetic Compatibility	CNS 13438, FCC Part-15 Class A, ICES 003 Class A, EN 55022 Class A, VCCI Class A, AS/NZS CISPR 22 Class A
Electromagnetic Immunity	EN 55024
CE certification	2004/108/EC, 2006/95/EC, 2011/65/EC
Approvals	CB, CE, C-Tick, EAC, FCC, VCCI
Environmental compliance	RoHS compliant, WEEE compliant
Compliance notes	There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request.
Compliance link	https://sp.ts.fujitsu.com/sites/certificates
Warranty period	3 years
Spare Parts availability	5 years

In addition to Fujitsu ETERNUS JX60, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu ETERNUS JX60, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/eternus

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>

Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see http://ts.fujitsu.com/terms_of_use.html

Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

Contact

FUJITSU LIMITED

Website: www.fujitsu.com/eternus

2020-05-25 WW-EN