

Fujitsu recommends Windows.

Data Sheet

FUJITSU Workstation CELSIUS M730

Your "Thoroughbred" Workstation

If you're looking for reliable performance when using demanding applications, the FUJITSU CELSIUS M730 single-processor desktop workstation delivers just excellent performance. It can be individually configured, helping you to enhance your productivity. It features best-in-class noise emissions of only 20 dB(A) for a quiet and efficient working environment. Comprehensive ISV certifications ensure your applications run smoothly. Finally, the convenient cold plug access at front simplifies subsequent expansion.



Performance

Higher productivity

- Future Intel® Xeon® processors, high performing graphics subsystems, quad-channel memory technology and high-speed hard disk drives

Ergonomics

Noise-reduced system engineered in Germany

- Optimized thermal management, low-noise chassis and silent fans

Reliability

System stability for the complete lifecycle

- High product standards thanks to top-quality components and comprehensive testing in certified in-house laboratories for 24/7 operation

Certification of workstation applications

Stability, compatibility and performance for the main workstation applications

- Comprehensive support for ISV applications and ease of integration into existing IT networks

Expandability

Excellent expandability for future demands

- Increased memory capacities of up to 128 GB



Components

	Intel® Xeon® processor E5 family featuring Intel® vPro™ Technology	
Operating systems		
Operating system	Windows 8.1 64-bit Windows 8 Pro 64-bit Windows 7 Professional 64-bit	Windows 8.1 64-bit Windows 8 Pro 64-bit Windows 7 Professional 64-bit
Operating system compatible	Windows® Server 2012 Windows 7 Professional 32-bit Windows® XP Professional x64 Edition Linux	Windows® Server 2012 Windows 7 Professional 32-bit Windows® XP Professional x64 Edition Linux
Operating system notes	Certified for Red Hat® Enterprise Linux Certified for SUSE Enterprise Desktop Certified for SUSE Enterprise Server For some configurations third party drivers are currently not available or configuration restrictions may apply. SCU ports are not supported for Windows® XP 32bit (restriction by Intel®). Therefore an additional storage controller (D2607 or D2616) is necessary. Limited Windows® XP support. Microsoft discontinued Windows® XP certification on system level, basic drivers via http://support.ts.fujitsu.com	Certified for Red Hat® Enterprise Linux Certified for SUSE Enterprise Desktop Certified for SUSE Enterprise Server For some configurations third party drivers are currently not available or configuration restrictions may apply. SCU ports are not supported for Windows® XP 32bit (restriction by Intel®). Therefore an additional storage controller (D2607 or D2616) is necessary. Limited Windows® XP support. Microsoft discontinued Windows® XP certification on system level, basic drivers via http://support.ts.fujitsu.com
Graphics		
	Ultra-high-end 3D: NVIDIA® Quadro® K5000, 4 GB, 1,536 cores, PCIe x16, 1x Dual Link DVI-I, DVI-D, 2x DisplayPort	
	Midrange 3D: NVIDIA® Quadro® K2000D, 2 GB, 384 cores, PCIe x16, 2x Dual Link DVI-I	
	Professional 2D: NVIDIA® NVS™ 510, 2 GB, 16 cores, PCIe 2.0 x16, 4x miniDP, 4x miniDP/DP Adapter	
	Professional 2D: NVIDIA® NVS™ 315, 1 GB, 48 cores, PCIe 2.0 x16, 2x LFH59 (DP/DVI-I)	
	Professional 2D: NVIDIA® NVS™ 315 fanless, 1 GB, 48 cores, PCIe 2.0 x16, 2x LFH59 (DP/DVI-I)	
	Professional 2D: NVIDIA® NVS™ 310, 512 MB, 16 cores, PCIe 2.0 x16, 2x DisplayPort	
	Remote Graphics: CELSIUS RemoteAccess Dual Card, PCIe x1, 2x miniDP, PCoIP	
	Remote Graphics: CELSIUS RemoteAccess Quad Card, PCIe x1, 4x miniDP, PCoIP	
Personal Supercomputing		
	Coprocesor: Intel® Xeon Phi™ Coprocessor 3120A, PCIe x16	
Hard disk drives (internal)		
	SSD SATA III Premium, 512 GB, 2.5-inch	
	SSD SATA III Premium, 256 GB, 2.5-inch	
	SSD SATA III Premium, 128 GB, 2.5-inch	
	SSD SATA III, 256 GB, 2.5-inch	
	SSD SATA III, 128 GB, 2.5-inch	
	HDD SAS, 15,000 rpm, 300 GB, 2.5-inch	
	HDD SAS, 10,000 rpm, 900 GB, 2.5-inch	
	HDD SAS, 10,000 rpm, 600 GB, 2.5-inch	
	HDD SAS, 10,000 rpm, 300 GB, 2.5-inch	
	HDD SATA III, 10,000 rpm, 1,000 GB, 2.5-inch, business critical	
	HDD SATA III, 10,000 rpm, 500 GB, 2.5-inch, business critical	
	HDD SATA III, 7,200 rpm, 4,000 GB, 3.5-inch, business critical	
	HDD SATA III, 7,200 rpm, 3,000 GB, 3.5-inch, business critical	
	HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch, business critical	
	HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch, business critical	
	HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch, business critical	
	HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch	
	HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch	
	HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch	
Hard disk notes	*Disk imaging software of the customer must be 4k sector size / advanced format ready One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. 24/7 ready (business critical HDDs required)	

Drives (optional)	BD Triple Writer SATA slim (tray) DVD-ROM DVD Super Multi MultiCard Reader 24in1 USB 2.0 3.5"
SCSI / SAS Controller	RAID 5/6 Ctrl. 6 Gbit/s 8 ports int. 512 MB Cache RAID 0/1 Ctrl. 6 Gbit/s 8 ports int.
Interface add on cards/components (optional)	WLAN 802.11 a/g/n (2x2), (dedicated regions only, not for Indonesia) USB 3.0 PCIe x1 Serial Interface FH Gigabit Ethernet PCIe x1, DS eSATA Interface Dual serial card PCIe x1 Dual 10 Gigabit Ethernet PCIe x8
Base unit	CELSIUS M730 CELSIUS M730 power
Mainboard	
Mainboard type	D3128
Formfactor	ATX
Chipset	Intel® C602
Processor socket	Socket R
Processor quantity maximum	1
Memory slots	8 DIMM (DDR3) ECC/non-ECC
Supported capacity RAM (max.)	128 GB
Memory notes	In configurations with 4 GB and more the visible memory may be reduced to approximately 3.5 GB or less (for 32-bit operating systems) and configurations with 8 GB the visible memory may be reduced to approximately 7.5 GB or less (depending on system configuration). Large memory may lead to long boot times. When using a 32-bit operating system the maximum of memory might be 900 MB.
LAN	Built-in 10/100/1,000 MBit/s Intel® 82579 LM
BIOS version	AMI Aptio 4.6
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)
Audio type	On board
Audio codec	Conexant CX20642
Audio features	High Definition Audio
I/O controller on board	
Serial ATA total	6
thereof SATA III	2
SATA RAID support	0, 1, 10, 5
SAS Controller type	optional upgrade to 4 ports, Intel C604
SAS RAID support	0, 1, 10
Interfaces	
Audio: in (rear)	1
Audio: out (rear)	1
Audio: in	1
Audio: out	1
Internal speakers	1
USB 2.0 total	11
USB 3.0 total	2
USB front	4 (2x USB 3.0)

Interfaces

USB rear	6
USB internal	3, thereof 1 type A
Mouse / Keyboard (PS/2)	1 / 1
Ethernet (RJ-45)	1
Interface Module notes	Anytime USB charge functionality

Input device / components

	Optical USB tilt wheel mouse
Input devices (optional)	Optical USB/PS2 tilt wheel mouse Space Explorer USB Keyboard

Drive bays

Drive bays total	12
2.5-inch internal bays	8
3.5-inch internal bays	4
3.5-inch external bays	2
5.25-inch external bays	2

Slots

PCI-Express 3.0 x4 (mech. x8)	2 x (312 mm / 12.29 inch) Full height
PCI-Express 3.0 x16	2 x (312 mm / 12.29 inch) Full height
PCI-Express 2.0 x4 (mech. x16)	1 x (312 mm / 12.29 inch) Full height
PCI (32-bit / 33 MHz)	2 x (312 mm / 12.29 inch) Full height

Electrical values

Power consumption note	190 W depending on configuration	250 W depending on configuration
Rated voltage range	100 V - 240 V	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz	50 Hz - 60 Hz
Operating voltage range	90 V - 264 V	90 V - 264 V
Operating line frequency range	47 Hz - 63 Hz	47 Hz - 63 Hz
Max. output of single power supply	500 W up to 90% efficiency	800 W up to 90% efficiency
Power factor correction/active power	active	
Power supply output	1 graphics power rail (6pin connector / 17A@12V)	2 graphics power rails (6pin connector / 17A@12V)

Noise for standard configuration (HDD, ODD, FDD)

Related Processors for noise	Intel® Xeon® E5-1620v2 w/ Nvidia® NVS 300	Intel® Xeon® E5-1620v2 w/ Nvidia® NVS 300
Standard noise emission	2x2 GB, HDD, ODD, Windows According to ISO 7779:2010, ECMA-74	2x2 GB, HDD, ODD, Windows According to ISO 7779:2010, ECMA-74
Standard noise notes / description	A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A))	A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A))
Standard noise operation mode: CPU 50% load	3.5 B / 20 dB(A) Bystander position	3.5 B / 20 dB(A) Bystander position
Standard noise operation mode: CPU 90% load	3.5 B / 20 dB(A) Bystander position	3.5 B / 20 dB(A) Bystander position
Standard noise operation mode: HDD load	3.6 B / 20 dB(A) Bystander position	3.6 B / 20 dB(A) Bystander position
Standard noise operation mode: Idle mode	3.5 B / 20 dB(A) Bystander position	3.5 B / 20 dB(A) Bystander position
Standard noise operation mode: ODD load	4.5 B / 28 dB(A) Bystander position	4.5 B / 28 dB(A) Bystander position
Standard noise operation mode: Office applications 2.0	3.5 B / 20 dB(A) Bystander position	3.5 B / 20 dB(A) Bystander position
Blue angel noise emission according certification	According to ISO 7779:2010, ECMA-74 for max. possible configuration	According to ISO 7779:2010, ECMA-74 for max. possible configuration
Blue angel noise notes / description	A-weighted sound power level Lwad (in B); 1B = 10dB	A-weighted sound power level Lwad (in B); 1B = 10dB

Noise for standard configuration (HDD, ODD, FDD)

Blue angel noise operation mode: HDD load	3.8 B = 38 dB (A)	3.8 B = 38 dB (A)
Blue angel noise operation mode: Idle mode	3.8 B = 38 dB (A)	3.8 B = 38 dB (A)
Blue angel noise operation mode: ODD load	4.6 B = 46 dB (A)	4.6 B = 46 dB (A)

Dimensions / Weight / Environmental

Dimensions (W x D x H)	186 x 481 x 430 mm
Operating position	Vertical / horizontal
Weight	18 kg
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35 °C (50 - 95 °F)
Operating relative humidity	5 - 85 % (relative humidity)

Compliance

Product	CELSIUS M730	CELSIUS M730 Power
Model	ETNA_S-D3128	
Germany	GS depending on configuration	
Europe	CE	
USA/Canada	cCSAus FCC Class B	
Global	RoHS (EU & China) Medical EMC standard IEC60601-1-2 in combination with medical kit Microsoft Operating Systems (HCT / HCL entry / WHQL) WEEE (Waste electrical and electronic equipment) ENERGY STAR® 6.0 (dedicated regions, depending on configuration) EPEAT® Gold (dedicated regions)	
Compliance link	http://globalsp.ts.fujitsu.com/sites/certificates	

Additional Software

Additional software (preinstalled)	Workplace Protect (secure authentication solution) McAfee Multi Access Security (anti-virus and internet security software; 60 days trial version) Microsoft Office (buy license to activate the pre-installed Microsoft Office)
Additional software (optional)	Drivers & Utilities DVD (DUDVD) Windows® 8 and Windows® 7

Security

Physical Security	Kensington Lock support Eye for padlock Intrusion switch Integrated cabinet lock (optional)	Kensington Lock support Eye for padlock Intrusion switch Integrated cabinet lock (optional)
System and BIOS Security	Write protect option for the Flash EPROM Boot protection for floppy disk / CD drive and write protection for floppy disk drive Dynamic USB security for full hardware USB protection Control of all USB interfaces Trusted platform module (TPM 1.2) EraseDisk	Write protect option for the Flash EPROM Boot protection for floppy disk / CD drive and write protection for floppy disk drive Dynamic USB security for full hardware USB protection Control of all USB interfaces Trusted platform module (TPM 1.2) EraseDisk
User Security	User and supervisor BIOS password Access protection via external SmartCard reader (optional) Access protection via internal SmartCard reader (optional)	User and supervisor BIOS password Access protection via external SmartCard reader (optional) Access protection via internal SmartCard reader (optional)

Manageability

Manageability technology	DeskUpdate Driver management iAMT 8.0 (depending on CPU)
Manageability software	DeskView Client DeskView Instant BIOS Management DeskView Integration for Symantec Management Platform

Manageability

DeskView components	Inventory Management BIOS Management Driver Management Security Management Alarm Management
Supported standards	WMI BootP (made4you) PXE WoL (Wake on LAN)
Manageability link	http://www.fujitsu.com/fts/manageability

Miscellaneous

	Rack mountable (5U)	Rack mountable (5U)
Spare part availability	5 years	5 years

Packaging information

Packaging dimension (mm)	397 x 597 x 555 mm	397 x 597 x 555 mm
Packaging dimension (inch)	15.63 x 23.5 x 21.85 inch	15.63 x 23.5 x 21.85 inch
Max. quantity / pallet	16	16
Packaging notes	printed user documentation is bleached in chlorine free process	printed user documentation is bleached in chlorine free process

Warranty

Warranty period	3 years (depending on country)
Warranty type	Bring-In / Onsite Service (for countries within region FTS CEMEA&I, for all other countries depending on local regulations, minimum: 3 years material warranty)
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty

Product Support Services - the perfect extension

Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	5 years after end of product life
Service Weblink	http://www.fujitsu.com/fts/services/support

Recommended Accessories

Display P27T-7 LED

Enjoy perfect picture quality with 3.7 Mio pixels, outstanding ergonomics and usability as well as comfortable energy saving solutions of this 68.5 cm (27-inch) widescreen FUJITSU P Line Display. Order Code: S26361-K1442-V140

Display P27T-7 UHD

For pixel, color and performance-hungry professionals using demanding applications, look no further than the FUJITSU P27T-7 UHD Display. It provides outstanding picture quality with Ultra High Definition (UHD) resolution, also known as 4k. Picture in Picture (PiP), unrivalled ergonomics, a multitude of UHD supporting interfaces and manageability make this the perfect choice. Order Code: S26361-K1564-V140

Blue LED Mouse GL9000

Blue LED Mouse GL9000 comes in a slim design with proven Fujitsu engineering quality. The state-of-the-art blue LED sensor enables ultra precise switchable resolution at 1,000, 1,500 and 2,000 dpi. Blue LED Mouse GL9000 makes your life easier because it's tailor-made for right handed users. It just feels great in your hand. Order Code: S26381-K438-L100

SpaceMouse™ Pro

Using the SpaceMouse™ Pro 3D mouse to navigate 3D models or environments is as simple as holding them in your hand. A slight movement of the controller cap delivers easy and precise control. SpaceMouse™ Pro is a companion to the traditional mouse and is operated with the free hand. Your traditional mouse hand is free to select, create and edit.

Order Code:
S26381-K459-L100

Keyboard KB900

The KB900 is a very flat keyboard with extra low keys and spill-resistant protection. The elegant design and top-quality construction makes the KB900 the ideal input device for any PC or Notebook user. If you accidentally spill some water or coffee onto the keyboard, this special construction helps the liquid to flow away.

S26381-K560-L4** (**:
Country specific variation)

More information

Fujitsu OPTIMIZATION Services

In addition to the FUJITSU Workstation CELSIUS M730, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about the FUJITSU Workstation CELSIUS M730, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts/CELSIUS

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
© 2015 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions
Website: www.fujitsu.com/fts
2015-10-02 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
© 2015 Fujitsu Technology Solutions GmbH